

# Bodine BSL06M5UAK55LDI1 Compact LED Emergency Driver



Bodine BSL06M5UAK55LDI1 Compact LED Emergency Driver

Benefits:

- New compact design for space-limited LED applications
- Test switch with plenum rated cable
- Smart Charger Technology for low energy consumption
- Manually deactivate emergency operation for shipping or storing product via test switch
- Emergency operation automatically reactivates when AC power is reapplied
- Meets Title 20 CEC (California Energy Commission) efficiency standards
- Automatic code-compliant testing
- Controlled power for predictable discharge
- Color-coded, poke-in terminals to enhance wiring accuracy and ease of assembly/installation
- BSL06M5 includes: Wires, mounting plate adapter, wire extraction tool or screws
- RoHS compliant

## Specifications

UL Listed for US and Canada

Listed to UL924 and tested to CSA 22.2 No. 141

Field or Factory Installation (Indoor and Damp)

Output Class 2 Compliant

Illumination Time

90 Minutes

Initial Light Output

Up to 780 lumens\*

Full Warranty

5 Years (NOT pro-rata)

Universal Input Voltage

120-277 VAC, 50/60 Hz

Output Voltage

15 – 54 VDC

Output Power

6.0 W initial (regulated)

Test Switch / Charging Indicator Light

Test Switch with Plenum Rated Cable\*\*

35.43" (900 mm)

Battery

High-Temperature, Maintenance-Free

Lithium Ion Battery

7- to 10-Year Life Expectancy

Recharge Time

24 Hours

Temperature Rating

Ambient : 0°C to +55°C (32°F to 122°F)

Case: Tc (max): 65°C

Dimensions

4.21" x 3.00" x 1.18" (107 mm x 76 mm x 30 mm)

Mounting Center 4.59" (117 mm)

Weight

0.75 lbs. (0.34 kg)

For other items like the Bodine BSL06M5UAK55LDI1 Compact LED Emergency Driver [click here](#).

For more information on Bodine's line of lighting solutions [click here](#).