

Bodine BSL17C-C2ST LED Emergency Driver



Bodine BSL17C-C2ST LED Emergency Driver. Self-Testing
Emergency LED Driver. Self-Testing Class 2 Output.

Benefits

- Listed for field or factory installation – UL 924 and CSA C22.2 No. 141

Emergency Lighting Compliant

- Automatic Self-Testing to ensure code compliance
- Smart Charger Technology for low energy consumption
- Meets Title 20 CEC (California Energy Commission) efficiency standards
- Class 2 output – UL 1310 Certified, CSA 22.2 No 223-M91 compliant
- Controlled power for predictable discharge
- Emergency mode initial lumen output of up to 975 lumens
- 15 – 50 VDC for wide range of LED loads
- Universal input (120 through 277 VAC, 50/60 Hz)
- RoHS Compliant

Specifications

UL Listed

Listed to UL924 and tested to CSA 22.2, No. 141

For Field or Factory Installation

(Indoor and Damp)

Illumination Time

90 Minutes

Full Warranty

5 Years (NOT pro-rata)

Universal Input Voltage

120-277 VAC, 60 Hz

AC Input Power

3.0 W (Maximum)

Output Voltage

15.0 – 50.0 VDC

Output Power

7.5 W (Initial)

Test Switch/Charging Indicator Light

2 W – ITS (2-Wire illuminated test switch)

Battery

High-Temperature, Maintenance-Free

Nickel-Cadmium Battery

7- to 10-Year Life Expectancy

Recharge Time

24 Hours

Temperature Rating

Ambient : 0°C to +55°C (32°F to 131°F)

Case: Tc (max): 65°C

Dimensions

12.0" x 2.4" x 1.5"

(304 mm x 60 mm x 38 mm)

Mounting Center 11.5" (292 mm)

Weight

4.3 lbs. (1.95 kg)

For other items like the Bodine BSL17C-C2ST LED Emergency

Driver [click here](#).

For more information on Bodine's line of lighting solutions [click here](#).