

HJS-1/2-FM/SM – VIVE WIRELESS HUB



This is the Vive Wireless Hub. The Vive hub provides a connection point for Lutron Vive devices such as PowPak wireless dimming and switching modules, PowPak Wireless Fixture Controllers, PowPak 20 A Relay Modules, Maestro Wireless dimmers and switches, Pico remote controls, Radio Powr Savr occupancy sensors, and daylight sensors. For a complete list of compatible devices, see spec sheet (downloadable PDF). **Click here to see the Lutron Vive story.**

Features:

- Communicates with controls on a floor using Lutron wireless Clear Connect technology (range radius of 71 ft [22 m]).
- Distributed system architecture. Wireless sensors and controls must be located within 60 ft. (18 m) line of sight, or 30 ft. (9 m), through walls, of the associated device.
- Supports timeclock events based on both sunrise and sunset or fixed time-of-day.
- Integrated multi-color LED provides feedback on what mode the hub is in.
- Contact Closure Inputs for integration with devices by others including devices for Title 24 Automatic Demand Response

WattStopper IT-200 INTELITIMER PRO LOGGER



This is the IntelITimer Pro logger. The IntelITimer Pro (IT-200) is a revolutionary occupancy and light logger that establishes the energy saving potential when using occupancy sensors. With this versatile tool, spaces for lighting control use can be pinpointed and savings can be verified.

The IT-200 records a log entry every time there is a change in either the occupancy status or lighting status and stores a detailed history of these events for retrieval by PC. It utilizes passive infrared technology to detect occupancy. It observes the light level through a clear, plastic light pipe to determine if lights are on or off. The logger distinguishes artificial lighting from natural lighting to give accurate “lights-on” readings. To log data, a user places the logger so that its lens has a clear view of the workspace and the light-pipe aims towards the nearest light fixture. **Check out Wattstopper DLM products here.**

- Reports show graphs of occupancy and lighting and projects savings and statistical information
- Users set logging parameters for more accurate savings projection
- Powered by a lithium battery, with an extended life span of approximately ten years

- Small and lightweight for ease of use and portability
- Installs quickly and conveniently and requires no wiring
- IT-ProSoft 2.0 operates in six languages (English, French, German, Spanish, Swedish, and Norwegian) with appropriate currency/ date/time formats, and energy and HVAC defaults
- Occupancy detection LED helps users confirm that logger is detecting motion in desired space
- Light level LED helps users set logger to identify the on and off lighting levels of different locations
- The LEDs work for a 60 second test period to preserve battery life