

***Discontinued* LR-HWLV-HVAC – TOUCHPRO WIRELESS TOUCHSCREEN THERMOSTAT**



This is the Touchpro Wireless Touchscreen Thermostat. **Check out the RadioRA 2 collection [here](#).**

***Discontinued* RD-RD-277-XX – RadioRA 2 REMOTE DIMMER**



THIS PRODUCT HAS BEEN DISCONTINUED

This is the RadioRA 2 remote dimmer. **Check out the RadioRA 2 [products page here](#).**

- RadioRA 2 Maestro dimmers incorporate advanced features such as fade on/fade off, delayed long fade to off, and

rapid full on.

- RadioRA 2 Maestro local controls include a Front Accessible Service Switch (FASS) for safe lamp replacement.
 - Use Lutron Designer (Claro or Satin Colors) wallplates or designer-style wallplates from other manufacturers.
-

90681X – WIDE SLIDE DIMMER



This is the wide slide dimmer. **Check out the Pass & Seymour products.**

- LEED Contribution
 - Maximum ratings are for continuous full load.
 - Many 1000W models fit standard Decorator plates.
 - RFI suppression built in.
 - Full-On bypass.
 - Preset ON/OFF switch automatically returns controlled lights to preset level without readjusting dimmer setting.
 - 600W maximum rated dimmers can be ganged without de-rating.
-

90683X – SLIDE DIMMER



This is the slide dimmer. **Check out the Pass & Seymour products.**

- LEED Contribution
- Maximum ratings are for continuous full load.
- Many 1000W models fit standard Decorator plates.
- RFI suppression built in.
- Full-On bypass.
- Preset ON/OFF switch automatically returns controlled lights to preset level without readjusting dimmer setting.
- 600W maximum rated dimmers can be ganged without de-rating.

94003X – ROTARY FAN SPEED CONTROL



This is the rotary fan speed control. Since the development of

variable fan speed controls, many fans have made an annoying humming noise when their speed was reduced. Through the use of specially designed capacitive circuitry, these units can control fans at 3- or 4-speed levels in slide, rotary, and dual styles with virtually no fan motor noise. **Check out the Pass & Seymour products.**

94004X – ROTARY FAN SPEED CONTROL



This is the rotary fan speed control. Since the development of variable fan speed controls, many fans have made an annoying humming noise when their speed was reduced. Through the use of specially designed capacitive circuitry, these units can control fans at 3- or 4-speed levels in slide, rotary, and dual styles with virtually no fan motor noise. **Check out the Pass & Seymour products.**

94084X – WIDE SLIDE SERIES

FAN SPEED CONTROL



This is the wide slide series fan speed control. Since the development of variable fan speed controls, many fans have made an annoying humming noise when their speed was reduced. Through the use of specially designed capacitive circuitry, these units can control fans at 3- or 4-speed levels in slide, rotary, and dual styles with virtually no fan motor noise. **Check out the Pass & Seymour products.**

94301X — ROTARY FAN SPEED CONTROL



This is the rotary fan speed control. **Check out the Pass & Seymour products.**

- Full range speed control.
- Utilizes standard toggle wall plates.
- 100 percent tested for symmetry for extended fan life.
- Ground lead provided.

- Ferrite bar coil choke for excellent RFI suppression.
-

94315X – ROTARY DUAL FAN SPEED/DIMMER CONTROL



This is the rotary dual fan speed/dimmer control. **Check out the Pass & Seymour products.**

- Fits one gang box.
 - Controls both fan speed and light level.
 - Decorator styling.
-

94581X – WIDE SLIDE SERIES FAN SPEED CONTROL



This is the wide slide series fan speed control. **Check out the**

Pass & Seymour products.

- Full range speed control.
 - Compatible with Decorator wall plates.
 - 100 percent tested for symmetry for extended fan life.
 - Ground lead provided.
 - Ferrite bar coil choke for excellent RFI suppression.
-

97030X – WALL BOX DECORATOR ROTARY TIMER



This is the wall box decorator rotary timer. **Check out the Pass & Seymour products.**

- Units with “Hold” feature may be turned counter-clockwise to hold the load on without timing function.
- Turning clockwise causes unit to time load off after desired time delay.
- Quiet operation.
- Time range from 5 minutes to 12 hours.
- Available with or without hold.
- Decorator styling.
- Easily installed.
- Large head screw terminals.
- Accurate to +/- 5 percent.
- Motor rated.
- Energy saving.

Acuity LC&D Blue Box 30A Relay Normally Closed LCDACC SL30NCL



Acuity LC&D Blue Box 30A Relay Normally Closed LCDACC SL30NCL

This is the LC&D additional relay blue box LT (NCL). **Check out our Acuity products here.**

- Single-pole latching relay
- Can be defaulted to be normally closed(NC) or normally open(NO)
- High-connectivity terminal blocks allows up to two #8 AWG wires per plug
- Better efficiency since no energy is used to hold the contacts
- Call or order double-pole option