

97030X – WALL BOX DECORATOR ROTARY TIMER



This is the wall box decorator rotary timer. **Check out the Pass & Seymour products.**

- Units with “Hold” feature may be turned counter-clockwise to hold the load on without timing function.
- Turning clockwise causes unit to time load off after desired time delay.
- Quiet operation.
- Time range from 5 minutes to 12 hours.
- Available with or without hold.
- Decorator styling.
- Easily installed.
- Large head screw terminals.
- Accurate to +/- 5 percent.
- Motor rated.
- Energy saving.

CW-1-XX – CLARO WALLPLATE 1- GANG



- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving


CW-2-XX – CLARO WALLPLATE 2-GANG



- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™

- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
 - Full line of wiring devices in designer style opening
 - Blank inserts available for Gloss colors (DV-BI-) and Satin colors (SC-BI-)
 - Customize your designer wallplate with engraving
-

CW-3-XX – CLARO WALLPLATE 3-GANG



This is the Claro Wallplate 3-Gang. **Check out the [RadioRA 2 products page here](#).**

- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving
- More finishes available. Please contact us for pricing

CW-4-XX – CLARO WALLPLATE 4-GANG




This is the Claro Wallplate 4-Gang. **Check out the [RadioRA 2 products page here](#).**

- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving

CW-5-XX – CLARO WALLPLATE 5-

GANG



This is the Claro Wallplate 5-Gang. **Check out the [RadioRA 2 products page here](#).**

- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving

CW-6-XX – Claro Wallplate 6-Gang



DIM-0/10-2CH – 2 CHANNEL LOW VOLTAGE DIMMING MODULE



This is the 2 channel low voltage dimming module.

- Provide two channels of 0-10V dimming for up (40) ballasts per channel (80 total).
 - Combine a two-pole line voltage switching module and a two channel 0-10V dimming module. This completely disconnects the line voltage load from the source automatically when the dimmer is set to 0%.
 - Dimming Modules communicate with the Master Interface to report:
 - The dimmer's current dimming level (0-100%)
 - The line source state (available or off)
 - The communication status (active / not available)
 - The module's "health" (if the module is defective)
 - Interchangeable with all other RD style relay and dimming modules, providing a higher level of flexibility than currently available in the market
-

DIM1-2W/3W-120/277 – LINE VOLTAGE & 3-WIRE DIMMING MODULE



This is the Line Voltage & 3-Wire Dimming Module.

- Software configurable for either forward or reverse phase control.
- Utilize a relay ahead of the dimmer for complete disconnection from the source voltage when the dimmer is off.
- Dimming Modules are completely compatible with 3-wire fluorescent dimming ballasts (Hot, Dimmed Hot and Neutral).
- Dimming Modules communicate with the Building Management Server to report:
 - The dimmer's current dimming level (0-100% on)
 - The line source state (available or off)
 - The communication status (active / not available)
 - The module's "health" (if the module is defective)


FP-G1 – 1-GANG DECORATOR-

STYLE FACEPLATE




This is the 1-gang decorator-style faceplate. The FP-G line of decorator-style faceplates from Crestron® is available in several designer colors with a smooth or textured finish. The faceplates are offered in 1-gang, 2-gang, 3-gang, and 4-gang styles to suit every installation need. **Check out the Züm by Crestron products here.**

GRX-CBL-346S-500 – 500 ft GRX 3000/HOME WORKS CTRL CABLE



- Non-Plenum rated cable for use with the following Lutron systems
 - GRAFIK Eye ® 3000
 - GRAFIK Eye ® QS
 - Energi Savr Node TM

GRX-CBL-46L-250 – 250 ft GRAFIK 4000/6000 CTRL CABLE



- Non-Plenum rated cable for use with the following Lutron systems
 - GRAFIK Eye ® 3000
 - GRAFIK Eye ® QS
 - Energi Savr Node TM