CAR-20-DDTR-XX — Dual Dimming Tamper Resistant Receptacles and Plug 20 A



- Permanently installed internal tamper resistant shutter mechanism capable of resisting insertion of foreign elements into the device
- Back wire installation capable
- Plug may be used with standard receptacles and with new receptacles designed for dimming use
- Plug uses split-shell design for easy wiring and the ability to control cord exit direction

CW-1-XX — CLARO WALLPLATE 1-GANG



Can be used in conjunction with the following dimmer(s)


- and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving

CW-2-XX — CLARO WALLPLATE 2-GANG



- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors (DV-BI-) and Satin colors (SC-BI-)
- Customize your designer wallplate with engraving

CW-3-XX — CLARO WALLPLATE 3-GANG




This is the Claro Wallplate 3-Gang. Check out the RadioRA 2 products page here.

- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving
- More finishes available. Please contact us for pricing

CW-4-XX — CLARO WALLPLATE 4-


GANG



This is the Claro Wallplate 4-Gang. Check out the RadioRA 2 products page here.

- Can be used in conjunction with the following dimmer(s) and switch(es): Maestro®, Maestro IR®, Maestro Wireless®, Pico™ wireless control, Spacer System®, Diva®, Lyneo® Lx, Skylark®, Skylark Contour™
- All Lutron® wallplates are screwless, seamless and have no visible hardware; the front plate securely snaps into the alignment adapter plate
- Full line of wiring devices in designer style opening
- Blank inserts available for Gloss colors and Satin colors
- Customize your designer wallplate with engraving

CW-6-XX — Claro Wallplate 6-Gang



DIM1-2W/3W-120/277 — LINE VOLTAGE & 3-WIRE DIMMING MODULE



This is the Line Voltage & 3-Wire Dimming Module.

- Software configurable for either forward or reverse phase control.
- Utilize a relay ahead of the dimmer for complete disconnection from the source voltage when the dimmer is off.
- Dimming Modules are completely compatible with 3-wire fluorescent dimming ballasts (Hot, Dimmed Hot and Neutral).
- Dimming Modules communicate with the Building Management Server to report:
 - The dimmer's current dimming level (0-100% on)
 - The line source state (available or off)
 - The communication status (active / not available)
 - The module's "health" (if the module is defective)

FP-G1 — 1-GANG DECORATOR-STYLE FACEPLATE




This is the 1-gang decorator-style faceplate. The FP-G line of decorator-style faceplates from Crestron® is available in several designer colors with a smooth or textured finish. The faceplates are offered in 1-gang, 2-gang, 3-gang, and 4-gang styles to suit every installation need. Check out the Züm by Crestron products here.

GRX-CBL-346S-500 — 500 ft GRX 3000/HOME WORKS CTRL CABLE




- Non-Plenum rated cable for use with the following Lutron systems
 - GRAFIK Eye ® 3000
 - GRAFIK Eye ® QS
 - Energi Savr Node TM

GRX-CBL-46L-250 - 250 ft GRAFIK 4000/6000 CTRL CABLE



- Non-Plenum rated cable for use with the following Lutron systems
 - GRAFIK Eye ® 3000
 - GRAFIK Eye ® QS
 - Energi Savr Node TM

GRX-CBL-46L-500 - 500 ft GRAFIK 4000/6000 CTRL CABLE



- Non-Plenum rated cable for use with the following Lutron systems
 - GRAFIK Eye ® 3000

- GRAFIK Eye ® QS
- Energi Savr Node TM

GRX-IT-WH — 4-Scene Wireless Remote Control Infrared Transmitter



- Uses wireless infrared communications to select and adjust scenes.
- Scene selection buttons select four scenes.
- Off button turns all lights off.
- Master raise/lower button brightens or dims all lighting zones.
- Works with GRAFIK Eye 3000 and 4000 Series Control Units or any Wallstation with an infrared receiver.