Bodine B100 Emergency Ballast

Convenient Code-Compliance Dry or Damp Locations End-of-Lamp-Life Compatible Product order number: B100 (metal case)

Benefits: • Dry or Damp Locations • Emergency mode lumen output up to 450 lumens • End-of-Lamp-Life Compatible

Dimensions 9.4” x 2.4” x 1.5” (mounting center – 8.9”)

Specifications:

UL Listed (UL924 Emergency Lighting Equipment)
Factory or Field Installation
(Dry or Damp)
Illumination Time
90 Minutes (Standard)
Initial Light Output
350 – 450 Lumens
Full Warranty
1 Year (NOT pro-rata)
Dual Input Voltage
120/277 VAC, 60 Hz
AC Input Current
280 mA
AC Input Power Rating
2.5 Watts
Test Switch
Single Pole
Battery
High-Temperature, Maintenance-Free

Nickel-Cadmium Battery
7- to 10-Year Life Expectancy
Battery Charging Current
280 mA
Recharge Time
24 Hours
Charging Indicator Light
LED
Ballast Temperature Rating (Ambient)
0°C to +50°C (32°F to 122°F)
(Damp Location)
0°C to +55°C (32°F to 131°F)
(Dry Location)
Dimensions
9.4” x 2.4” x 1.5” (238 mm x 60 mm x 38 mm)
Mounting Center 8.9” (226 mm)
Weight
2.1 lbs. (1.13 kg)