

Bodine LP600STU Emergency Ballast



Bodine LP600STU Emergency Ballast provides automatic code compliant testing and is compatible with H0 T5 and T8 lamps. Low Profile for Space Limited Fixtures. 1300 Initial Lumen Output.

UL LISTED for US and Canada
Factory or Field Installation
(Indoor and Damp)

Illumination Time
90 Minutes

Initial Light Output
600 – 1325 Lumens @ 25°C

Full Warranty
5 Years (NOT pro-rata)

Universal Input Voltage
120 Through 277 VAC, 50 or 60 Hz

AC Input Current
55 mA

AC Input Power Rating
5.0 Watts

Test Switch / Charging Indicator Light
Two-Wire Illuminated Test Switch (2W-ITS)*

* The 2W-ITS is a Class 2 device.

Battery

High-Temperature, Maintenance-Free

Nickel-Cadmium Battery

7- to 10-Year Life Expectancy

Battery Charging Current

150 mA

Recharge Time

24 Hours

Charging Indicator Light

LED

Temperature Rating (Ambient)

0°C to +50°C (32°F to 122°F)

Dimensions

21.5" x 1.18" x 1.18"

(546.1 mm x 30 mm x 30 mm)

Mounting Center 22.1" (561 mm)

Weight

3.3 lbs. (1.5 kg)

Model LP600STU is warranted for five (5) full years from date of purchase. Please see detailed warranty information on the Signify official website.

For other items like the Bodine LP600STU Emergency Ballast [click here](#).

For more information on Bodine's line of lighting solutions [click here](#).