

H-MOUNT-SM — REPLACEMENT SURFACE-MOUNT INSTALLATION ADAPTER



This is the Replacement Surface-mount Installation Adapter for Lutron Vive system. It has Knockouts for 3/4 in (19 mm) conduit. **Click here to see the Lutron Vive story.**

HIGHLIGHTS:

- The Vive Basic package provides switching and occupancy / vacancy sensing of multiple load types.
- Lutron patented Clear Connect RF Technology works through walls and floors.
- Controls include Front Accessible Service Switch (FASSTM) for safe lamp replacement.
- Two-wire installation for any retrofit application.
- Power failure memory: If power is interrupted, the control will return to its previously set level prior to interruption.

System Communications and Capacity

- Maestro Wireless controls communicate with the Pico remote controls and Radio Power Savr
- sensors through radio frequency (RF).
- Receives wireless inputs from up to 10 Pico remote controls, 10 Radio Powr Savr occupancy / vacancy sensors, and 1 Radio Powr Savr daylight sensor
- Maestro Wireless local controls must be located within

60 ft. (18 m) line of sight or 30 ft. (9 m) through walls, of Radio Power Savr sensors.

- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m)
- through walls, of a Pico remote control.
- Up to 10 Maestro Wireless controls can be configured to work together.

Sensors can be assigned to multiple switches.