

LR-3B-H-SW – RadioRA 2 VISOR CONTROL TRANSMITTER



This is the RadioRA 2 visor control transmitter. RadioRA 2 Visor Controls allow lights, shades /draperies, and other equipment to be controlled from the car with just a touch of a button on a Visor Control Transmitter or a HomeLink® compatible visor control. Up to ten (10) Transmitters can be used with a Visor Control Receiver. Pre-printed and blank labels are included with the Visor Controls for naming scenes or buttons on both the Receiver and the Transmitter. **Check out the RadioRA 2 products page here.**

- Each output can be controlled locally at the Receiver or remotely by a Transmitter or keypad button.
 - The Receiver 'Keypad' or 'Inputs' buttons can be programmed to light and shades /draperies. Design Features
 - Full or Flash security options.
 - The Transmitter can remotely control the 'Keypad', 'Security Input', and 'Outputs' buttons on the Receiver.
 - RR-VCRX-WH: Visor Control Receiver (Sold Separately)
-

PD-5S-DV – 5A 2-BUTTON RF SWITCH



- Provides switching of multiple load types, occupancy/vacancy sensing, and daylight harvesting.
- RF Technology works through walls and floors.
- Two-wire switch perfect for retrofit applications.
- Power failure memory: If power is interrupted, the control will return to its previously set level prior to interruption.

PICO-SM-KIT – SCREW-MOUNT KIT FOR PICO® WIRELESS CONTROL



Mounting Considerations:

- Mounting of any RF devices on or in close proximity to a metal surface will drastically reduce the effective

range of radio signal transmission or reception.

- All RF devices must be mounted on non-conductive materials to ensure proper performance.
 - If you wish to mount your PicoR wireless control to a metal surface, the PICO-MOUNT-1-XX-CPN5733 will be required in order to maintain proper RF performance.
-

PJ2-2B-GXX-XXX – PICO WIRELESS CONTROL 2 BUTTON



This is a Pico Wireless Control 2 button. **Click here to see the Lutron Vive story.**

- Provides control for the following:
 - Caséta Wireless controls
 - Energi Savr NodeT, Quantum , and myRoomT systems, through the use of a QS sensor module (QSM)
 - Vive TM systems, including:
 - Maestro Wireless controls
 - PowPak ® modules
 - GRAFIK Eye QS wireless systems
 - HomeWorks QS wireless systems
 - Maestro Wireless controls
 - PowPak modules
 - RadioRA 2 systems
 - Serena RF remote control shades

- Sivoia QS wireless systems
- Control available in a variety of button marking options.
- Easy reconfiguration for use as:
 - Handheld remote
 - Wall-mount control (with or without faceplate; faceplate adapter kit sold separately)
 - Car visor control (car visor clip sold separately)
 - A table top control (table top pedestal sold separately).

HIGHLIGHTS:

- The Vive Basic package provides switching and occupancy / vacancy sensing of multiple load types.
- Lutron patented Clear Connect RF Technology works through walls and floors.
- Controls include Front Accessible Service Switch (FASSTM) for safe lamp replacement.
- Two-wire installation for any retrofit application.
- Power failure memory: If power is interrupted, the control will return to its previously set level prior to interruption.

System Communications and Capacity

- Maestro Wireless controls communicate with the Pico remote controls and Radio Power Savr
- sensors through radio frequency (RF).
- Receives wireless inputs from up to 10 Pico remote controls, 10 Radio Powr Savr occupancy / vacancy sensors, and 1 Radio Powr Savr daylight sensor
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m) through walls, of Radio Power Savr sensors.
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m)
- through walls, of a Pico remote control.

- Up to 10 Maestro Wireless controls can be configured to work together.
 - Sensors can be assigned to multiple switches.
-

PJ2-2BRL-GXX-XXX – PICO WIRELESS CONTROL 2 BUTTON w/ RAISE/LOWER



This is a Pico Wireless Control 2 button w/ raise/lower. **Click here to see the Lutron Vive story.**

- Provides control for the following:
 - Caséta Wireless controls
 - Energi Savr NodeT, Quantum , and myRoomT systems, through the use of a QS sensor module (QSM)
 - Vive TM systems, including:
 - Maestro Wireless controls
 - PowPak ® modules
 - GRAFIK Eye QS wireless systems
 - HomeWorks QS wireless systems
 - Maestro Wireless controls
 - PowPak modules
 - RadioRA 2 systems
 - Serena RF remote control shades
 - Sivoia QS wireless systems

- Control available in a variety of button marking options.
- Easy reconfiguration for use as:
 - Handheld remote
 - Wall-mount control (with or without faceplate; faceplate adapter kit sold separately)
 - Car visor control (car visor clip sold separately)
 - A table top control (table top pedestal sold separately).

HIGHLIGHTS:

- The Vive Basic package provides switching and occupancy / vacancy sensing of multiple load types.
- Lutron patented Clear Connect RF Technology works through walls and floors.
- Controls include Front Accessible Service Switch (FASSTM) for safe lamp replacement.
- Two-wire installation for any retrofit application.
- Power failure memory: If power is interrupted, the control will return to its previously set level prior to interruption.

System Communications and Capacity

- Maestro Wireless controls communicate with the Pico remote controls and Radio Power Savr
- sensors through radio frequency (RF).
- Receives wireless inputs from up to 10 Pico remote controls, 10 Radio Powr Savr occupancy / vacancy sensors, and 1 Radio Powr Savr daylight sensor
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m) through walls, of Radio Power Savr sensors.
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m)
- through walls, of a Pico remote control.
- Up to 10 Maestro Wireless controls can be configured to

work together.

- Sensors can be assigned to multiple switches.

PJ2-3B-GXX-L01 – PICO WIRELESS CONTROL 3 BUTTON



This is a Pico Wireless Control 3 button. **Click here to see the Lutron Vive story.**

- Provides control for the following:
 - Caséta Wireless controls
 - Energi Savr NodeT, Quantum , and myRoomT systems, through the use of a QS sensor module (QSM)
 - Vive TM systems, including:
 - Maestro Wireless controls
 - PowPak ® modules
 - GRAFIK Eye QS wireless systems
 - HomeWorks QS wireless systems
 - Maestro Wireless controls
 - PowPak modules
 - RadioRA 2 systems
 - Serena RF remote control shades
 - Sivoia QS wireless systems
- Control available in a variety of button marking options.
- Easy reconfiguration for use as:

- Handheld remote
- Wall-mount control (with or without faceplate; faceplate adapter kit sold separately)
- Car visor control (car visor clip sold separately)
- A table top control (table top pedestal sold separately).

HIGHLIGHTS:

- The Vive Basic package provides switching and occupancy / vacancy sensing of multiple load types.
- Lutron patented Clear Connect RF Technology works through walls and floors.
- Controls include Front Accessible Service Switch (FASSTM) for safe lamp replacement.
- Two-wire installation for any retrofit application.
- Power failure memory: If power is interrupted, the control will return to its previously set level prior to interruption.

System Communications and Capacity

- Maestro Wireless controls communicate with the Pico remote controls and Radio Power Savr
- sensors through radio frequency (RF).
- Receives wireless inputs from up to 10 Pico remote controls, 10 Radio Powr Savr occupancy / vacancy sensors, and 1 Radio Powr Savr daylight sensor
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m) through walls, of Radio Power Savr sensors.
- Maestro Wireless local controls must be located within 60 ft. (18 m) line of sight or 30 ft. (9 m)
- through walls, of a Pico remote control.
- Up to 10 Maestro Wireless controls can be configured to work together.
- Sensors can be assigned to multiple switches.

PJN-2B-GXX-L01 – 2 BUTTON PICO WIRELESS CONTROL W/ NIGHTLIGHT



This is the 2 button Pico wireless control w/ nightlight. **Check out the [RadioRA 2 products page](#) here.**

- Provides control for the following:
 - Maestro WirelessR controls
 - PowPakR Modules
 - Energi Savr NodeT and QuantumR systems, through the use of a QS sensor module (QSM)
 - GRAFIK EyeR QS wireless systems
 - RadioRAR 2 systems
 - HomeWorksR QS wireless systems
 - CasetaT Wireless dimmers
- Battery-powered. Requires no wiring.

PJN-3BRL-GXX-L01 – PICO

WIRELESS CONTROL W/ NIGHTLIGHT – 3 BUTTON W/ RAISE/LOWER



This is the Pico wireless control w/ nightlight – 3 button w/ raise/lower. **Check out the RadioRA 2 products page here.**

- Provides control for the following:
 - Maestro WirelessR controls
 - PowPakR Modules
 - Energi Savr NodeT and QuantumR systems, through the use of a QS sensor module (QSM)
 - GRAFIK EyeR QS wireless systems
 - RadioRAR 2 systems
 - HomeWorksR QS wireless systems
 - CasetaT Wireless dimmers
- Battery-powered. Requires no wiring.

TSUI-WM – TOUCHSCREEN USER INTERFACE



This is the Touchscreen user Interface.

- Color touch screen computers that provide custom graphical user interfacing.
- Displays are available in three configurations:
 - 7" TFT 800×480 WVGA, color display
 - 10.4" TFT 800×600 SVGA, color display
 - 13.3" TFT 1280×800 WXGA, color display
- Displays include internal flash for local storage of graphic pages.