

3-4082

Wall Mount, Outdoor



Features

Housing

Die-cast Aluminum with Powder Coated Finish
 Finish Option: -06 White

Electrical

High Power Factor, Low THD
 Built-in with or without Photo Cell

Lamp


Built-in LED Module: More Color Temperature Option - 4000K, 5000K
 GU24 CFL Type: More Color Temperature Option - 2700K, 4000K

Certification

UL/cUL or ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Warranty on LED Driver and Module



Built-in LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Shade	Dimension (H x W X E)	Energy Star	Note
3-4082D-xxxxK	120V	15W	3000K / 80	850	PC	9.8" x 7.8" x 4.2"	Yes	
3-4082D-xxxxK-11W	120V	11W	3000K / 80	500	PC	9.8" x 7.8" x 4.2"	Yes	Driver On Board
3-4082D-3000K(JA8)	120V	15W	3000K / 90	680	PC	9.8" x 7.8" x 4.2"	---	Dimmable

GU24 Type

Model	Input Voltage	Input Wattage	Finish	Shade	Lamp	Dimension (H x W X E)	Energy Star
3-4082PG-05	120V	18W	Black	PC	1 x 18W GU24	9.8" x 7.8" x 4.2"	---