

DC028 DC032

Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel, -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD

Lamp


Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
 Color Temperature Option – 3000K, 3500K, 4000K, 5000K
 CFL Type: Circline or T8 Lamp (Color Temperature Option – 2700K, 4000K)

Certifications

UL/cUL or ETL/cETL Listed, Energy Star

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (L X W X H)	Energy Star
DC028D-3000K	120V ~ 277V	35W	3000K	> 80	3485	28.3" x 14.1" x 4.4"	Yes
DC028D-4000K	120V ~ 277V	35W	4000K	> 80	3660	28.3" x 14.1" x 4.4"	Yes
DC032D-3000K	120V ~ 277V	46W	3000K	> 80	4470	32.3" x 18.1" x 4.3"	Yes
DC032D-4000K	120V ~ 277V	46W	4000K	> 80	4700	32.3" x 18.1" x 4.3"	Yes

MCT Type (Multiple Color Temperature Models)

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ) / CT	Dimension (L X W X H)	Energy Star
DC032D-MCT	120V ~ 277V	46W	Adjustable	> 80	4470 / 3000K	32.3" x 18.1" x 4.3"	Yes
DC032D-MCT-28W	120V ~ 277V	28W	Adjustable	> 80	2720 / 3000K	32.3" x 18.1" x 4.3"	Yes

CFL Type

Model	Input Voltage	Input Wattage	Shade	Lamp	Dimension (L X W X H)	Energy Star
DC032-xxxxK	120V	64W	Acrylic	2 x 32W T9 Cir.	32.3" x 18.1" x 4.3"	---
DC032-417 HPF	120V ~ 277V	68W	Acrylic	4 x F17T8, 17W	32.3" x 18.1" x 4.3"	---
DC028-317 HPF	120V ~ 277V	51W	Acrylic	3 x F17T8, 17W	28.6" x 14.1" x 4.4"	---